

Siskiyou Golden Speedway 2022

FWD-Sport Compact Racing Rules

Rules apply at ALL TIMES car is on track!!

Safety Equipment:

_____ Snell rated helmet SA 2010, 2015, or 2020 required. Fireproof gloves, shoes, and neck brace recommended. Rollbar and padding required in driver compartment. Driver side window net required, minimum 16" X 20" ribbon or mesh style. Net must be mounted to roll cage. Recommended safety belts no more than 2 years old, required 2" or wider. Battery must be mounted in cab with kill switch within reach of driver and safety officials. Current fire extinguisher in reach is also required. **Age limit is 14, unless otherwise approved!**

Body Chassis:

Front wheel drive 4+ seater, 3 or 4 cylinders with no more than 150 horsepower. Must be OEM appearing body. **No convertibles or 2-seater sports cars**, Unaltered OEM floor pan. Hood and trunk hatches must be securely fastened and accessible from outside. **ALL** doors must be securely welded, bolted, or chained shut. **ALL** glass must be removed. Dash and stereo can either remain or be removed. Maximum 7" visors on front and rear allowed. Numbers must be 4" wide and 18" tall or bigger. Numbers must be clearly visible on both sides and the roof. Minimum weight 2200 lbs.

Vehicle Identification Number:

_____ The V.I.N. number must remain intact and unaltered in at least 2 OEM locations. Any missing V.I.N will not compete.

Driver Compartment:

_____ Minimum three (3) windshield bars in front of driver, screen optional, no screen means safety goggles required. Aluminum high back racing seat required.

MUST BE SECURELY MOUNTED TO ROLL CAGE ONLY!!! Use $\frac{3}{8}$ or larger bolts to mount to roll cage. **ALL** flammable equipment and loose parts must be removed (air bags).

Front and rear firewalls must be in place with no holes. (Rear seat panel recommended) Interior must remain open. Raceceiver highly recommended. No 2-way radios to be used for driver communication.

FUEL SYSTEM. _____ Must be complete OEM system if tank is located in front of rear axle. If tank is behind rear axle, it must be replaced with a maximum 8- gallon fuel cell located and mounted in trunk. Minimum one-inch square tubing and 2-2-inch straps mounting tank. A fire wall between driver and tank must be installed if using fuel cell, as well as a non-spill and cut off switch.

Suspension and Steering:

_____ Removable steering wheel recommended. No center steering. Must remain OEM column. Springs and shocks must remain in stock location. Adjustments ok (aftermarket springs ok if fitted properly) Clamps and rubber pucks ok. *Any mods must be safe and approved.* No more than 3-degree camber.

Tires and Wheels:

_____ **13,14,15,16 in” steel wheels only.** No more than 8” wide. Passenger car tires only min 60 series. ***NO mud or snow tires (studded type).*** Racing tires and alterations ok.

Brakes:

_____ Brakes must be OEM and operative at all wheels! No brake shut off or bias adjuster.

Exhaust:

_____ Stock manifold or header ok. Exhaust must extend past the driver and must include at least one muffler.

Battery:

_____ Must be mounted in driver compartment. Must be securely mounted with metal strapping with positive terminal protected. (Recommended marine battery box)
Car must start unaided or start in the back of the pack during race.

Engine Compartment:

_____ Engine and radiator must be OEM in stock location for that year, make, and model. May use solid engine mounts or chains. Engine and components must match and be OEM for that year, make, and model of the car used and must match V.I.N.

_____ Must be OEM crank, rods, valve sizes, stroke, head etc. **NO** racing heads. **NO** high performance or sports car engines. **NO** superchargers or turbos, or rotary engines. **NO unapproved alterations allowed!!!**

Transmission:

_____ Transaxle must be OEM for make and model used. Manual to auto swaps ok if same model is used. Must be unaltered and operate in every gear. Flex plate, flywheel, clutch assembly, and torque converter must remain unaltered. **No trans coolers in driver compartment.**

Bumpers and rub rails:

_____ Rubber bumper covers must be in place and attached. Front and rear tow hooks **mandatory.** May have one bar horizontal- max 1.75" OD- tying front horns together ahead of radiator. One 1" bar may be added to protect the radiator. Must be behind bumper, no wider than OEM frame horns. Maximum 1" wide by 2" tall or Lexan rub rails allowed, bolted flush to body.

Rollcage:

_____ 4-point roll cage full perimeter with rear down bars to trunk. Must use 1.5" OD with no less than 0.095 wall required. Dash bar required. Cage must be electrically welded and attached to floor pan with minimum 4"X4" 1/4 "steel plates. Bottom plates also required, and plates must be bolted together with minimum 3/8 bolts (4). **NO IRON, GALVANIZED PIPE, OR FITTINGS, SQUARE TUBING, BRAZING, OR Soldering ALLOWED.** Gussets should be at every 90 degree, or 2 opposite in each square

Door Bars:

_____ Driver side minimum 3 horizontal and 2 vertical. Passenger side minimum 2 horizontal, 2 vertical (or one diagonal in place of vertical). Minimum 1.5 OD 0.0095 thickness steel plate welded to outside of driver door. Must be welded into place with minimum 12"X16" and minimum 0.049 thickness and must be visible for inspection.

OPTIONAL passenger seat!!_

If installing a passenger seat, door bars must be 3 horizontal and two vertical and be bent to the door skin same as driver side. Also must include 5 point harness, high back aluminum race seat, window net and grab bar, or faux steering wheel. **MUST BE AS SAFE OR SAFER THAN DRIVER.** Passenger is also required to use sfi race suit and snell approved helmet, gloves, and race shoes highly recommended!!!!

—

